

# Contract Range Metal Non-Fire Rated Access Panel

Feb 2022

## Product



## INSTALLATION

- Prepare a clear trimmed and protected opening in the structure 5mm larger than the ordered panel
- Create cutouts for the pivot hinges approx. 10x6mm so the pivot operation is clear
- Turn up fixing tabs and screw fix using suitable screws through the pre punched holes to all four sides of the frame
- For beaded frame fix through face of frame and scrim tape as per plaster stop bead
- To maintain even gaps between door and frame complete the operation with door in frame where possible
- To remove the door from frame remove the pivot hinge plate with a cross headed screwdriver
- When refitting and after installation ensure the pivot hinge plates are fully located and if fitted, the retaining chains are in place

## FEATURES & BENEFITS

- Contract range low cost protected opening for ceilings and walls
- Lightweight narrow profile
- Pivoting door frame and frame
- Powder coated white finish, can be over painted on site to suit surroundings
- Available in beaded frame with perforated flange or picture frame with solid flange
- Discrete invisible keyhole option is recommended with this range
- Bespoke panels available on request

## Product Details

Standard Sizes (mm)	
Size	150x150; 200x200; 300x300 450x450; 550x550; 600x600
Note	Hinge side always stated first
Colour	White (Ral9010) powder coated 20% gloss finish
Material	1.0 & 1.2mm Zintec electro-galvanized mild steel
CODE Picture frame	AC11NFAC
CODE Beaded	AC12NFAC

## Hinge and lock mechanism

Factory fitted removable pivot plate with inserted steel pins locating into holes in the frame. Square drive operated lock riveted to the return fold of the door tray with tongue locating over frame. Keyhole concealed by the invisible keyhole system.

Operation - Using the T key supplied push the invisible keyhole system aside, engage the key into the locks and open and close while supporting the door. The invisible keyhole system springs back automatically to conceal the keyhole.

