

Technical Data Sheet

Double Airbrick ICV5733G

Nov 2023

PRODUCT

W	RAL9010
B	RAL8017
BE	RAL1001
T	RAL2001



PRODUCT DETAILS

Colour	Buff, Terracotta, Grey, Black, Brown, White
Code	ICV5733T—Terracotta ICV5733BE—Beige ICV5733BR—Brown ICV5733WH—White

Free Area	15,360mm ² per 9x6 brick vent unit
Size	220mm x 90mm
Material	High impact Polystyrene

USES

- In conjunction with the ducting system 220x90mm
- To provide ventilation through external walls to the building interior.
- Used in conjunction with straight through cavity wall sleeve.

FEATURES & BENEFITS

- Free area of 15,360mm² per 9x6 air brick
- Unique stepped front grille reduces the entry of wind driven rain
- Available in wide range of colours to match various brick types, buff, terracotta, brown and white
- Female adaptor for connection to outside of system 220 ducting.
- Very tough and robust high impact polystyrene
- Durable and totally resistant to decay
- Compliant with Appendix Q characteristics for HRV

Max/min operating temperature - +60°C to -15°C

Individual Weight - 258g

INSTALLATION

- Always use in conjunction with ICON system 220 ducting. 220x90mm
- Remove 2 x standard brick and replace with airbrick.

