

Technical Data Sheet

Slate & Tile Vent Adaptor

PRODUCT—ITT13 150mm adaptor



USES

- For use with both ISG5 slate and ITG5 tile ventilation system.
- For remedial work on existing roofs
- Suitable for roof pitches between 20° and 60°

FEATURES & BENEFITS

- Can be installed as required during slating process
- Snap fitted to the underside of the slate or tile vent
- Driving rain and deluge rain resistance
- AA fire rating to BS476:Part3:2004
- Suitable for use with Heat recovery systems requiring a 150mm adaptor

Airflow performance TT13 150mm diameter spigot

50m³/hr at 0.3Pa	100m³/hr at 1.0Pa
200m³/hr at 4.2Pa	300m³/hr at 9.5Pa
500m³/hr at 27.4Pa	

PRODUCT—IGV110 100mm adaptor



USES

- For use with all G range slate and tile ventilation system
- For remedial work on existing roofs
- Suitable for roof pitches between 20° and 60°
- For use as terminals for soil vent stacks or mechanical extract ventilation ducts.

FEATURES & BENEFITS

- Can be installed as required during slating process
- Snap fitted to the underside of the slate or tile vent
- Driving rain and deluge rain resistance
- AA fire rating to BS476:Part3:2004

Airflow performance IGV110 100mm diameter spigot

	IG1	IG3	IG5
54m³/hr	18Pa	2.5Pa	0.8Pa
108m³/hr	70Pa	11Pa	2.6Pa
216m³/hr	262Pa	42.5Pa	11.5Pa



Underlay Opening Protector

