

Internal Hit & Miss Grille

Technical Data Sheet

Nov 2023

PRODUCT



Uses

- To cover the inner opening on the cavity sleeve and provide an aesthetically acceptable appearance, while maintaining a free air flow.

INSTALLATION

- Internal grilles should be positioned over the internal opening of the cavity sleeve and fixed to the wall using screws and wall plugs
- Never block or restrict the flow of air through these ventilators
- Do not use hit & miss grilles when ventilating a gas or heat producing appliance
- We recommend using our external cowls to help reduce draughts caused by wind blast

FEATURES & BENEFITS

- Adjustable background ventilators for rooms
- Aesthetically pleasing
- Integral Flyscreen with concealed fixings
- Flush face and low profile vent
- UV stable
- Suitable for new build or Retro-fit
- Not suitable for boilers, stoves and fires.
- Easy installation
- Mechanically fixed
- Durable and resistant to decay

Product Details

9x3 Hit & Miss vent

Size	271(L) x 95mm (H)
Ventilation Free Area	4400mm ² 44cm ²
Colour	White
Code	IHM93

9x6 Hit & Miss vent

Size	271(L) x 171mm (H)
Ventilation Free Area	8600mm ² 86cm ²
Colour	White
Code	IHM96

9x9 Hit & Miss vent

Size	271(L) x 247mm (H)
Ventilation Free Area	13000mm ² 130cm ²
Colour	White
Code	IHM99

