

Slate & Tile Vent Adaptor

Technical Data Sheet

IGV110 110mm adaptor



Compatible - IG3/IG5 slate and tile vents

Pipe diameter - 110mm

Fire - AA Fire rating to BS476:Part3:2004

Airflow performance IGV110

	IG3	IG5
54m³/hr	2.5Pa	0.8Pa
108m³/hr	11Pa	2.6Pa
216m³/hr	42.5Pa	11.5Pa

IGVTT9 125mm adaptor



Compatible - IG3/IG5 slate and tile vents

Pipe diameter - 125mm

Fire - AA Fire rating to BS476:Part3:2004

Airflow performance ITT9

50m³/hr	@ 1.1Pa
100m³/hr	@ 4.1Pa
200m³/hr	@ 16.8Pa

IGVTT13 150mm adaptor



Compatible - IG3/IG5 slate and tile vents

Pipe diameter - 150mm

Fire - AA Fire rating to BS476:Part3:2004

Airflow performance ITT13

50m³/hr	@ 0.3Pa
100m³/hr	@ 1.0Pa
200m³/hr	@ 4.2Pa
300m³/hr	@ 9.5Pa
500m³/hr	@ 27.4Pa

KG99100 100mm adaptor



Compatible - 10k slate & inline tile vent

Pipe diameter - 100mm

Length - 375mm

Weight - 0.35kg

IT10 110mm adaptor



Compatible - IT10 slate vents

Pipe diameter - 110mm

Weight - 0.15kg

ISUA 110mm adaptor



Compatible - IGV11 slate and in-line tile

Pipe diameter - 110mm

Fire - AA Fire rating to BS476:Part3:2004

Airflow performance ISUA

54m³/hr (15lt/sec)	10Pa
108m³/hr (30lt/sec)	42Pa
216m³/hr (60lt/sec)	162Pa

KG979700 150mm adaptor



Compatible - Universal 20K tile vents

Pipe diameter - 150mm

Length - 200mm

Depth - 75mm

Weight - 0.35kg

KG968300 100mm adaptor



Compatible - Universal 15K tile vents

Pipe diameter - 100mm

Length - 170mm

Weight - 0.176kg

