

Universal Dry Verge U System

Technical Data Sheet

Jan 2022

PRODUCT



USES

The Dry Verge U systems is compatible with all large format interlocking concrete or clay roof tiles. Roof pitches 15-55° on new or refurbishment projects. Verges with or without bargeboards

FEATURES & BENEFITS

- Suitable for batten gauge between 260-345mm
- Long lasting, UV stable, reliable and virtually maintenance free.
- Flexible flaps on the ridge cap contour around the side of the verge piece helping prevent water ingress and infestation.
- Protects against wind uplift, water ingress and general deterioration
- Flexible polypropylene material
- Available in Black, Terracotta, Brown and Grey
- Simple and quick to install in all weather conditions
- Meets requirements of BS5534 and ICP2 for mechanical fixing
- Helps prevent entry of birds, large insects and vermin into the roof space.

INSTALLATION

1. Select the relevant verge system colour for your project
2. One verge piece is required for each roof tile in the sloping run
3. Verge pieces are universal and can be used on either the left or right verge
4. An eaves starter must be installed at the beginning of each sloping run of dry verge
5. Select the ridge shape for the apex of the system with the option of angled or half round. Carefully place over ridge tile and ensure flaps are sealed to verge pieces.



Universal dry verge pieces



Verge starter



Half round or Angled ridge end cap with flexible flap

