

Venduct Duo Solar Thermal Outlet

Technical Data Sheet

PRODUCT



PRODUCT DETAILS

Dimensions	Nozzle & Collar; 120mm high x 350mm long x 220mm wide Universal Base Tile: 425x450mm (inc Skirt)
Material	UV resistant Soft & Rigid PVC Nozzle: EPDM Sealing Collar - with silicon release paper & EPDM collar
Colour	Brown : 0247 Red: 0100 Slate Grey: 0429 Slate Version (Black): 0400



Sealing collar highly recommended to maintain weather tightness around pipe penetration in roof underlay.

Available in following sizes;
8-12mm; 15-22mm; 25-32mm
42-55mm; 50-70mm

USES

The Venduct Duo Solar Thermal Outlet is the ideal solution for allowing twin cables pass through the roof while fully protected from the rain and wind. The outer casing can be twisted variably at the side, so that laying direction of the pipes can be chosen freely.

FEATURES & BENEFITS

- Rain proof feed through of twin cables due to the combination with an elastic EPDM sealing collar
- Rotatable cap
- Low structural height
- Additional rubber seal for feeding through a cable of max. Ø 6mm
- Made with special UV resistant PVC
- EPDM collar heat-resistant up to 100°C
- Air and wind tight connection
- Easy installation
- Available in 3 colours to match roof finish
- Slate or tile kit available



Areas of Application

- Can be used for twin cables with diameter of 10-55mm
- Matches almost all customary clay concrete roof tiles, slates, beaver tail & fibre cement.
- Suitable for roof pitches 15° - 65°

